



Compression Fittings

Specifications: Lock Nut & Body - Black Polypropylene
 Maximum Working temperature - 80 Deg C/176 Deg F
 Maximum Working Pressure @ 20Deg C - 16 Atm./240psi

Male Adaptor



Code	Diam. MM	BSP Female
W702601	16	0.5"
W702602	16	0.75"
W702611	20	0.5"
W702612	20	0.75"
W702613	20	1"
W702621	25	0.5"
W702622	25	0.75"
W702623	25	1"
W702632	32	0.75"
W702633	32	1"
W702634	32	1.25"
W702643	40	1"
W702644	40	1.25"
W702645	40	1.5"
W702653	50	1"
W702654	50	1.25"
W702655	50	1.5"
W702664	63	1.25"
W702665	63	1.5"
W702666	63	2"

Female Adaptor



Code	Diam. MM	BSP Female
W703611	20	0.5"
W703612	20	0.75"
W703613	20	1"
W703621	25	0.5"
W703622	25	0.75"
W703623	25	1"
W703632	32	0.75"
W703633	32	1"
W703634	32	1.25"
W703643	40	1"
W703644	40	1.25"
W703645	40	1.5"
W703653	50	1"
W703654	50	1.25"
W703655	50	1.5"
W703664	63	1.25"
W703665	63	1.5"

Coupling



Code	Diam. MM	Diam. MM
W701600	16	16
W701611	20	20
W701622	25	25
W701633	32	32
W701644	40	40
W701655	50	50
W701666	63	63

Reducing Coupling



Code	Diam. MM	Diam. MM
W701610	20	16
W701621	25	20
W701632	32	25
W701642	40	25
W701643	40	32
W701653	50	32
W701654	50	40
W701663	63	32
W701664	63	40
W701665	63	50

Repair Coupling



Code	Diam. MM	Diam. MM
W700544	40	40
W700555	50	50
W700566	63	63
W700577	75	75

Tee



Code	Diam. MM	Diam. MM	Diam. MM
W704611	20	20	20
W704622	25	25	25
W704633	32	32	32
W704644	40	40	40
W704655	50	50	50
W704666	63	63	63

Reducing Tee



Code	Diam. MM	Diam. MM	Diam. MM
W704810	20	16	20
W704821	25	20	25
W704832	32	25	32
W704843	40	32	40
W704854	50	40	50
W704865	63	50	63



SPECIAL DISCOUNT PRICE AVAILABLE FOR KITS OR BULK ORDERS.
IF THE SIZE OR PRICE YOU REQUIRE IS NOT LISTED ABOVE,
PLEASE CONTACT OUR SALES OFFICE FOR A QUOTATION.



Compression Fittings

Specifications: Lock Nut & Body - Black Polypropylene
 Maximum Working temperature - 80 Deg C/176 Deg F
 Maximum Working Pressure @ 20Deg C - 16 Atm./240psi

Female Tee



Code	Diam. MM	BSP Female	Diam. MM
W714601	16	0.5"	16
W714602	16	0.75"	16
W714611	20	0.5"	20
W714612	20	0.75"	20
W714621	25	0.5"	25
W714622	25	0.75"	25
W714623	25	1"	25
W714632	32	0.75"	32
W714633	32	1"	32
W714634	32	1.25"	32
W714643	40	1"	40
W714644	40	1.25"	40
W714645	40	1.5"	40
W714654	50	1.25"	50
W714655	50	1.5"	50
W714665	63	1.5"	63
W714666	63	2"	63

Male Tee



Code	Diam. MM	BSP Male	Diam. MM
W713611	20	0.5"	20
W713622	25	0.75"	25
W713633	32	1"	32
W713644	40	1.25"	40
W713655	50	1.5"	50
W713666	63	2"	63

Elbow



Code	Diam. MM	Diam. MM
W705611	20	20
W705622	25	25
W705633	32	32
W705644	40	40
W705655	50	50
W705666	63	63

Flange Adaptor



Code	Diam. MM	Diam
W715655	50	1.5"
W715666	63	2"

Cap



Code	Diam. MM
W712620	25
W712630	32
W712640	40
W712650	50
W712660	63

Female Elbow



Code	Diam. MM	BSP Female
W707001	16	0.5"
W707011	20	0.5"
W707012	20	0.75"
W707021	25	0.5"
W707022	25	0.75"
W707023	25	1"
W707032	32	0.75"
W707033	32	1"
W707034	32	1.25"
W707043	40	1"
W707044	40	1.25"
W707045	40	1.5"
W707055	50	1.5"
W707056	50	2
W707065	63	1.5"

Male Elbow



Code	Diam. MM	BSP Female
W706601	16	0.5"
W706611	20	0.5"
W706612	20	0.75"
W706621	25	0.5"
W706622	25	0.75"
W706623	25	1"
W706632	32	0.75"
W706633	32	1"
W706634	32	1.25"
W706643	40	1"
W706644	40	1.25"
W706645	40	1.5"
W706655	50	1.5"
W706656	50	2
W706665	63	1.5"

Male Adaptor c/w Brass Thread Insert



Code	Diam. MM	BSP Male
W712822	25	0.75"
W712833	32	1"
W712844	40	1.25"
W712855	50	1.5"
W712866	63	2"

Universal Transition Coupling



Code	Diam. MM	Diam. MM
W709822	15/22	25
W709824	20/27	25
W709834	20/27	32
W709826	27/34	25
W708736	27/34	32

SPECIAL DISCOUNT PRICES AVAILABLE FOR KITS OR BULK ORDERS.
IF THE SIZE OR PRICE YOU REQUIRE IS NOT LISTED ABOVE,
PLEASE CONTACT OUR SALES OFFICE FOR A QUOTATION.